

**KOMEX**

STYLOWE CIEPŁO

## DANE TECHNICZNE GRZEJNIKA RENE POJEDYNCZY

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm3)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
600	236	4	48	87	550	3.5	2.5	104	173	217	300
600	294	5	48	87	550	4.5	3.0	130	216	271	300
600	352	6	48	87	550	5.5	3.5	155	259	325	300
600	410	7	48	87	550	6.0	4.0	181	302	379	300
600	468	8	48	87	550	7.0	4.5	207	345	433	300
600	526	9	48	87	550	7.5	5.0	233	389	487	300
600	584	10	48	87	550	8.5	5.5	259	432	541	600
600	642	11	48	87	550	9.5	6.0	285	475	595	600
1000	236	4	48	87	950	5.5	3.5	164	273	342	300
1000	294	5	48	87	950	7.0	4.5	205	341	428	300
1000	352	6	48	87	950	8.0	5.5	245	409	513	300
1000	410	7	48	87	950	9.5	6.0	287	478	599	300
1000	468	8	48	87	950	11.0	7.0	328	546	684	600
1000	526	9	48	87	950	12.0	8.0	368	614	770	600
1000	584	10	48	87	950	13.5	9.0	409	682	855	600
1000	642	11	48	87	950	15.0	9.5	450	750	940	800
1500	236	4	48	87	1450	8.0	5.0	239	398	499	300
1500	294	5	48	87	1450	10.0	6.5	299	498	624	300
1500	352	6	48	87	1450	12.0	8.0	358	597	749	600
1500	410	7	48	87	1450	13.5	9.0	418	697	873	600
1500	468	8	48	87	1450	15.5	10.0	478	796	998	800
1500	526	9	48	87	1450	17.5	11.5	538	896	1123	800
1500	584	10	48	87	1450	19.5	13.0	597	995	1247	1000
1500	642	11	48	87	1450	21.5	14.0	657	1095	1372	1000
1800	236	4	48	87	1750	9.5	6.0	284	473	593	300
1800	294	5	48	87	1750	11.5	7.5	355	592	742	600
1800	352	6	48	87	1750	14.0	9.0	426	710	890	600

1800	410	7	48	87	1750	16.0	10.5	497	828	1038	800
1800	468	8	48	87	1750	18.5	12.0	568	946	1186	1000
1800	526	9	48	87	1750	21.0	13.5	639	1065	1335	1000
1800	584	10	48	87	1750	23.0	15.0	710	1183	1483	1000
1800	642	11	48	87	1750	25.5	16.5	781	1301	1631	1000
2000	236	4	48	87	1950	10.5	6.5	316	526	659	600
2000	294	5	48	87	1950	12.7	8.5	394	658	824	800
2000	352	6	48	87	1950	15.5	10.0	473	789	989	800
2000	410	7	48	87	1950	17.7	11.5	552	920	1153	1000
2000	468	8	48	87	1950	20.5	13.5	631	1051	1318	1000
2000	526	9	48	87	1950	23.3	15.0	710	1183	1483	-
2000	584	10	48	87	1950	25.5	16.5	789	1314	1648	-
2000	642	11	48	87	1950	28.3	18.0	868	1446	1812	-

**W PRZYPADKU GRZEJNIKA W WERSJI POZIOMEJ NIE MA MOŻLIWOŚCI PODŁĄCZENIA GRZAŁKI ELEKTRYCZNEJ.**