

KOMEX

STYLÓWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA LENA ZDC

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych 1	rozstaw otworów montażowych 2	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
500	430	45-55	60-70	400	50	3,5	1,5	97	180	224	300
500	530	45-55	60-70	500	50	4,0	1,5	116	215	268	300
500	630	45-55	60-70	600	50	4,5	2,0	135	250	312	300
750	430	45-55	60-70	400	50	5,0	2,5	146	272	339	300
750	530	45-55	60-70	500	50	6,0	2,5	174	323	403	400
750	630	45-55	60-70	600	50	7,0	3,0	201	374	467	400
950	430	45-55	60-70	400	50	6,5	3,0	195	363	453	400
950	530	45-55	60-70	500	50	7,5	3,5	231	430	536	600
950	630	45-55	60-70	600	50	8,5	3,5	267	497	620	600
1150	430	45-55	60-70	400	50	8,0	3,5	232	431	538	400
1150	530	45-55	60-70	500	50	9,5	4,0	274	510	636	600
1150	630	45-55	60-70	600	50	10,5	4,5	317	589	735	600
1350	430	45-55	60-70	400	50	9,5	4,0	281	522	651	400
1350	530	45-55	60-70	500	50	11,0	4,5	332	618	771	600
1350	630	45-55	60-70	600	50	12,5	5,0	384	714	891	600
1550	430	45-55	60-70	400	50	11,0	4,5	317	590	736	600
1550	530	45-55	60-70	500	50	13,0	5,0	376	700	874	600
1550	630	45-55	60-70	600	50	15,0	6,0	435	810	1011	800